

Partial Translation of Japanese Unexamined Utility Model Publication (U) No. H03-70288

A vehicle sheet lining fabric which is a nonwoven fabric formed by three-dimensionally interlacing filaments, the fabric having a basis weight of 10 g/m^2 to 60 g/m^2 , a tensile stress in the machine direction of 0.2 kg/5 cm to 2.0 kg/5 cm at 5% elongation, a tensile stress in the transverse direction of not higher than 2.0 kg/5 cm at 5% elongation, a tensile strength of at least 2.0 kg/ 5 cm in both the machine and transverse directions, an elongation of at least 60% in both the machine and transverse directions, and a tear strength of at least 0.5 kg in both the machine and transverse directions.

Brief Description of the Drawing

Fig. 1 is a cross-sectional view of a vehicle sheet comprising the vehicle sheet lining fabric of the present model.

- 1. Outer material
- 2. Cushioning material
- 3. Lining fabric



Creation date: 09-12-2006

Indexing Officer: KTO - KIM THU TO

Team: ZZZFEP Dossier: 10589503

Legal Date: 09-07-2006

No.	Doccode	Number of pages
1	IDS	2
2	FOR	10 ·
3	FOR	70

Tot	tal	num	ber	of	page	es:	82

Remarks:

Order of re-scan issued on